

SILT-TREAT

EFFECTIVE and COST-CUTTING
continuous flow treatment system for construction sites

ST-15-CFS



ST-60-CFS

SILT-TREAT MODEL	TREATMENT CAPACITY	TANK DIMENSIONS	APP. WT (EMPTY)
ST-10-CFS	10m ³ per hr	2.2m L x 1.3m W x 2.5m Ht.	1.3 tonne
ST-15-CFS	15m ³ per hr	2.8m L x 2.2m W x 2.7m Ht.	1.6 tonne
ST-20-CFS	20m ³ per hr	3.3m L x 2.2m W x 2.7m Ht.	2 tonne
ST-30-CFS	30m ³ per hr	3.8m L x 2.2m W x 2.7m Ht.	2.5 tonne
ST-40-CFS	40m ³ per hr	4.2m L x 2.2m W x 2.7m Ht.	3.5 tonne
ST-50-CFS	50m ³ per hr	5 m L x 2.2m W x 2.7m Ht.	4.2 tonne
ST-60-CFS	60m ³ per hr	6 m L x 2.2m W x 2.7m Ht.	5 tonne
ST-80-CFS	80m ³ per hr	7 m L x 2.2m W x 2.7m Ht.	5.6 tonne



ST-10-CFS



ST-10-CFS



ST-20-CFS



ST-40-CFS

Stormwater Pte Ltd

For enquiries, please call Jimson Lee at +65 9796 2692 or email: swaf99@singnet.com.sg
Blk 150 Bishan St 11 #01-141 (2nd level) Singapore 570150 Tel: 6250 1718 Fax: 6250 1032